

Input	Phono RCA (PH1 & PH2)	<p>Input Impedance: 47 kOhm, unbalanced RIAA Response: 20 to 20 kHz + 1/-0.5 dB Distortion: THD + N less than 0.02 % @ 1 kHz Maximum Input Level: + 46 mV RMS, unbalanced, < 1 % THD Crosstalk: < - 60 dB, 20 to 20 kHz, 10 mV RMS, left-to-right</p>
	Line RCA (LN1-LN4)	<p>Input Impedance: 68 kOhm, unbalanced Frequency Response: 20 to 20 kHz +/- 0.5 dB Distortion: THD + N less than 0.003% @ 1 kHz Maximum Input Level: + 5V RMS, unbalanced, < 1 % THD Crosstalk: < -70 dB, 20 to 20 kHz, 2V RMS, left-to-right</p>
Isolators	3-Way Channel Isolator	<p>Filter Slope: 12 dB/oct Crossover Frequency: Bass >> 125 Hz <> Mid <> 4000 Hz << Treble Cut: -inf dB, Boost: + 9 dB</p>
	3-Way Master Isolator	<p>Filter Slope: 24 dB/oct Crossover Frequency: Bass >> 280 Hz <> Mid <> 4200 Hz << Treble Cut: -inf dB, Boost: + 9 dB</p>
Output	House XLR	<p>Output Impedance : 100 Ohm, balanced line-to-line Distortion: THD + N less than 0.003%, +4 dBu, 20 to 20 kHz, unity gain, 20 kHz BW SNR: 92 dB referenced to nominal level +4 dBu, A-weighting Max Output Level: + 26 dBu balanced, 20 to 20 kHz, 600 Ohm, < 1 % THD</p>
	Booth JACK	<p>Output Impedance: 100 Ohm, balanced line-to-line Distortion: THD + N less than 0.003 %, +4 dBu, 20 to 20 kHz, unity gain, 20 kHz BW SNR: 92 dB referenced to nominal level +4dBu, A-weighting Max Output Level: + 26 dBu balanced, 20 to 20 kHz, 600 Ohm, < 1 % THD</p>
	Rec Out RCA	<p>Output Impedance: 100 Ohm, unbalanced Distortion: THD + N less than 0.003 %, -10 dBV, 20 to 20 kHz, unity gain, 20 kHz BW SNR: 105 dB referenced to nominal level (-10 dBV), A-weighting Max Output Level: +18 dBV unbalanced, 20 to 20 kHz, 100 kOhm, < 1 % THD</p>
	Phones JACK	<p>Output Impedance: 68 Ohm Distortion: THD + N less than 0.005 %, 4.7 V RMS, 20 to 20 kHz, 300 Ohm Max Output Power: 1 W RMS into 70 Ohms, < 1 % THD</p>
Physical		<p>Power: 110/230 VAC Power consumption: 30 Watt maximum Dimensions: 300 × 235 × 152mm (11.81 × 9.25 × 5.98 inches) Weight: 3.5 kg (7.7 lbs) with built in PSU</p>
General information		<p>Official retail price: CHF 2'190 Warranty: 2 years</p>

* Every unit is tested by us with our test routine,
 built around an Audio Precision System Two 2322 Analyzer.